### mar plast group

## TRACTORS TP200 - TP200L ELECTRICPORTER

## FANTOZZI moving safe. at work



## General features and advantages

FANTOZZI TP200 borns to be an electric tractor for loading/towing goods with pedestrian driver. FANTOZZI TP200L is the model with longer loading platform for those companies who need more loading space and ask for a quick, safe and efficient vehicle.

#### Intensive use

The high numbers of scheduled working handlings and meanwhile the unexpected emergencies and precision, need reliable tools always versatile and available to carry-out continuous work granting high quality levels. Slim and strong FANTOZZI TP200 & TP200L are suitable to drive into small and complex ways; working proof resistant inside the stocking area and factory on flat floors.

#### Increase on productivity

FANTOZZI TP200 & TP200L tractors answer the modern concept of logistic, goods handling and people's transport which require more and more skilled and dedicated working instruments suitable to reach the best compromise between working time, working quality/precision, and operator's safety/satisfaction.

During handling of unpacked goods or single pieces - without pallets or loading units - FANTOZZI TP200 & TP200L produce a significant increase in productivity, it means much more work arranged shortly and saving of human resources.

#### Driving comfort

FANTOZZI TP200 & TP200L have comfortable pedestrian driving position, thanks to the ergonomic tiller handle and the great flexibility.

The driving control unit that can be operated with thumbs is placed inside the tiller for easier switch on/off.

By driving the TP200 & TP200L tractors, the operator stands longtime on safety and correct position while the loading/unloading operations are easier, thanks to the vehicle's handiness and the limited platform height.



Maximum safety for operator, goods and environment The modern concept of safety is not only limited to the operator but to the complete "system": operator, goods, environment.

FANTOZZI TP200 & TP200L are studied in accordance with current regulations as for accident-prevention, limited vibrations, industrial health, common protection etc, but mainly thinking on ethic responsibility and reliability as for working satisfaction and appreciation of human resources.

## Technical / manufacturing features

#### Motor

Equipped with 300W motor - Speed 8 Km/h - Loading capacity up to 100 Kg (model TP200L) - Towing capacity 200 Kg. max. (On request: 500W motor for driving on important grades).





Speed reducer 3 different reducing ratios are available: they allow the driving capacity on grades and speed capacity on long distances.

#### Chassis

Strong structure made of Fe37 with black embossing non-scratch epoxy painting. The structure reinforcements guarantee the maximum vehicle's reliability.






Electronic control unit
The electronic control unit allows the speed, braking, acceleration adjustments: these parameters customize the use of FANTOZZI Tractors.

#### Battery

TP200 & TP200L are equipped with two traction batteries 12V 51Ah (no battery maintenance), for 6 hours endurance. All kinds of batteries do not release fumes during the charge.






Built-in battery charger Built-in inside the vehicle, it allows everywhere quickly recharge and without additional costly devices.

#### Tiller handle

Easy-to-use, simple and ergonomic, the tiller handle includes:

- forward/backward control switch
- warning buzzer
- emergency button for emergency stop
- switching-on key.





Enlarged battery compartment FANTOZZI TP200 & TP200L are equipped with enlarged battery compartment in order to allow higher endurance (6 hours approx.).

Puncture-proof wheel
FANTOZZI TP200 & TP200L are
equipped with puncture-proof wheels.
Tyres are made by special superelastic
rubber mix studied to reach the
maximum safety for the vehicle.





Flexible tiller joint
Joint studied and manufactured for
double operation: 45° inclination: starts
the vehicle; straight position: stops the
vehicle.

Towing hook
Painted iron towing hook complete with
bolts and nuts for fixing.





Platform


No slipping aluminium platform 380 mm.
(900 mm model TP200L), allows the
loading of small references, adding
surplus to the operator's job.




## Technical features VDI 2198

s 1				Fantozzi	Fantozzi
1 %	1.2	Model		TP200	TP200L
= 1	1.3	Traction		Electric	Electric
Features 1	1.4	Type of driving		Pedestrian driver	Pedestrian driver
	1.5	Loading capacity	Q (t)	2	2
	1.9	Wheel axis	y (mm)	720	1200
pts 2	2.1	Weight including batteries	Kg	127	150
Weights		3 3 3 4 4 4 5 4 4 4 4 4 4 4 4 4 4 4 4 4			
2	3.1	Tyres (superelastic, pneumatic )		SE	SE
ture	3.2	Front wheel dimensions		3.00 - 4	3.00 - 4
1 9 -	3.3	Rear wheel dimensions		Ø 225	Ø 225
8/8	3.5	Front wheel number (x = traction)		1	1
heel	3.5.1	Rear wheel number (x = traction)		2	2
>	3.7	Rear wheel track	b <sub>11</sub> (mm)	430	430
4	4.7	Operator's protection height (cab)	h <sub>6</sub> (mm)	1270	1270
4	4.8	Operator's seat height (cab)	h <sub>6</sub> (mm)	/	/
4	4.12	Towing hook height	h <sub>10</sub> (mm)	90	90
4	4.13	Platform height (without loading)	h <sub>11</sub> (mm)	210	210
su *	****	Clearance	h <sub>11</sub> (mm)	115	115
Basic dimensions	4.16	Loading platform length	l <sub>3</sub> (mm)	380	900
Ĭ Ä	4.17	Loading platform width	b <sub>9</sub> (mm)	520	520
. <u>o</u> 4	4.19	Total length	I <sub>1</sub> (mm)	1020	1540
Bas	4.21	Total width	b <sub>1</sub> (mm)	520	520
		Working aisle width	(mm)	900	900
		Intersecting aisle width	(mm)	1300	2200
		Minimum rack width between 2 working aisles	(mm)	800	800
		90° Turning radius	(Wa mm)	1600	2440
5	5.1	Driving speed with full loading	km/h	4	4
s E	5.1.1	Driving speed without loading	km/h	4	4
ance 5	5.8	Max. grade with full loading	%	19	17
lu E	5.10	Service brake		Electromechanical + Mechanical	Electromechanical
* Performances	5.11	Parking brake		Electromechanical	Electromechanical
*		Emergency brake		Electromechanical	Electromechanical
		Driver detection sensor		Mechanical	Mechanical
<u> </u>	6.1	Traction motor - capacity KB 60 min	kW	0,3	0,3
of G	6.3	Battery		12V 51Ah	12V 51Ah
-E 6	6.4	Battery tension	UV	12V	12V
Electric motor	6.4.1	Battery capacity	K 5 Ah	51Ah	51Ah
	6.5	Battery weight	Kg	2 x 22,5	2 x 22,5
3	8.1	Kind of transmission		1:32	1:32
ω E	8.4	Average noise for the operator	dB (A)	< 70	< 70
Others	8.5	Towing hook		Manual	Manual
3	8.6	Steering gear		Mechanical	Mechanical
		Vibration to the operator		/	Mechanical

<sup>\*</sup> the performances refer to the vehicle in perfect conditions, with charged battery and regular motor maintenance





# Easy and safe movement Production increased.

Always walking effortless.
There is just one difference
between a walking man and a
walking man driving a TP200:
300 Kg. towed effortless and
without risks at 4 Km/h.

# Safe working. You can! You must!

#### **ELECTRICPORTER RANGE 2007**







**PLATFORMS** 



**SCOOTERS** 



**HOSPITAL** 













moving safe. at work

Fantozzi Electric Carts S.r.l. Via Rosa Luxemburg, 24 42010 Rio Saliceto (RE) - Italy Tel. +39 0522 647192 Fax +39 0522 699479 info@fantozzi.com sales@fantozzi.com www.fantozzi.com