

# PALLET TRUCKS

## GS Hand Pallet Trucks



### GS

The standard competitive and reliable solution for your daily needs

**Equipment:**

- 4 CURVES TILLER
- NYLON ROLLERS
- POLY RING STEERING WHEELS
- ON / OFF LOWERING VALVE



### GS EVO

The top choice. Full optional, max easiness of use and ergonomics, complete range of frame sizes, configurations and options



**Equipment:**

- 3D ERGONOMIC TILLER
- POLY ROLLERS
- POLY RING STEERING WHEELS
- PROPORTIONAL LOWERING VALVE
- ENTRANCE/EXIT ROLLERS

**Options:**

- QUICK LIFT
- COVERED TILLER
- ALL TYPES OF STEERING WHEELS AND ROLLERS
- ALL FORKS SIZES

**Complete range of solutions:**

- 3 TONS CAPACITY
- SILENT VERSION PIEK  CERTIFIED
- LOW PROFILE FORKS
- GALVANIZED
- STAINLESS STEEL 

L2: 400 mm

Aisle width (EPAL): 1835 mm

Drive and lift: manual



2500 kg



800,1150 mm



525 mm



2000-3000 kg



600-2000 mm



400-685 mm

## PX-GS/P Scale trucks



### PX 20-25

Accurate, competitive and reliable

**Equipment:**

- CAPACITY 2000 kg (PX20) 2500 kg (PX25)
- DIVISION: 2 kg (PX20) 0,5 kg (PX25)
- 4 LOAD CELLS
- ACCURACY 0,1% (PX20) 0,05% (PX25)
- POLY TANDEM ROLLERS
- POLY STEERING WHEELS
- RETRO ILLUMINATED LCD DISPLAY
- 3 CURVES TILLER
- ON / OFF LOWERING VALVE

Options PX25: • agile



### GS/P

The best accuracy and weighing features. Full range of options

**Equipment:**

- CAPACITY: 2500 kg
- DIVISION: 0,5 kg
- 4 LOAD CELLS
- ACCURACY: 0,05%
- POLY TANDEM ROLLERS
- POLY STEERING WHEELS
- LARGE LCD DISPLAY
- 3D ERGONOMIC TILLER
- PROPORTIONAL LOWERING VALVE
- IP65 PROTECTION

**Options:**

- QUICK LIFT
- CE-M HOMOLOGATION
- STAINLESS STEEL 
- PRINTER
- USB MEMORY
- agile

L2: 411 mm

Aisle width (EPAL): 1851 mm

Drive and lift: manual



2000-2500 kg



1185 mm



555 mm



2500 kg



1185 mm



555 mm

## HX Scissor Lifts



### HX10M

Compact and reliable with double cylinder system and quicklift to maximize efficiency and visibility and reduce operator effort

**Equipment:**

- QUICK LIFT
- PROPORTIONAL LOWERING VALVE
- POLY ROLLERS
- POLY STEERING WHEELS

Options: • STAINLESS STEEL 




### HX10E

The top electric scissor lift with double cylinder system to maximize efficiency and visibility. Available with autolevelling option to facilitate your work

**Equipment:**

- POLY ROLLERS
- RUBBER STEERING WHEELS
- BATTERY (C20) 12V/60Ah
- BATTERY CHARGER INCLUDED

**Options:**

- AUTOLEVELLING SYSTEM
- ON-BOARD CHARGER
- STAINLESS STEEL 

L2: 376 mm Aisle width (EPAL): 1779 mm

Drive and lift: manual

L2: 540 mm Aisle width (EPAL): 1948 mm

Drive: manual. Lift: electric



1000 kg



1150-2000 mm



540-680 mm



800 mm

## AGILE Semi electric pallet trucks



# agile **LI-ION** | agile **PLUS LI-ION**

The first innovative pallet truck with two traction wheels and full range of fork sizes

### AGILE Equipment:

- 2 RUBBER TRACTION WHEELS
- 3D ERGONOMIC TILLER
- ALL FRAMES SIZES
- POLY ROLLERS
- LI-ION BATTERY 36V/10,4Ah

### Options:

- QUICK LIFT
- FAST CHARGER
- DESK CHARGER (FAST)



### AGILE PLUS Equipment:

- 2 RUBBER TRACTION WHEELS
- 3D ERGONOMIC TILLER
- ALL FRAMES SIZES
- POLY ROLLERS
- EXTRA POWER LI-ION BATTERY 36V/12,8Ah
- ON-BOARD COMPUTER WITH DISPLAY
- MAX. SPEED SETTING

### Options:

- QUICK LIFT
- FAST CHARGER
- DESK CHARGER (FAST)
- SCALE
- IP54
- GALVANIZED\*
- STAINLESS STEEL\*

\*To be combined with IP54 option

L2: 450 mm

Aisle width (EPAL): 2063 mm

Drive: electric. Lift: manual



1200 kg



800-2000 mm



525-685 mm



5,3 km/h

## CX12 Electric pallet trucks



# CX12

The most compact EPT in the market (aisle width lower than HPT)

### Versions Available:

- STANDARD
- PLUS
- EVO



1200 kg



800-1150 mm



520 mm



4,8-5,0 km/h

L2: 360 mm Aisle width (EPAL): 1782 mm Drive and lift: electric

## CX14 Electric pallet trucks



# CX14

Robust compact and reliable with the highest performance in the category

### Versions Available:

- STANDARD
- PLUS
- EVO
- LI-ION



1400 kg



800-1150 mm





525-685 mm



4,8-6,0 km/h

L2: 410 mm Aisle width (EPAL): 1810 mm Drive and lift: electric

## CX12-14 Equipment

	STANDARD	PLUS	EVO	LI-ION
<b>MOTORWHEEL</b>	DC Motorwheel		AC Motorwheel <b>AC</b>	
<b>TILLER</b>	 <p>Tiller with:</p> <ul style="list-style-type: none"> <li>• Fingertip control</li> <li>• Turtle button</li> </ul>		 <p>Ergonomic tiller with:</p> <ul style="list-style-type: none"> <li>• Battery status indicator</li> <li>• Hourmeter</li> <li>• Turtle button</li> <li>• Boost button (CX14)</li> </ul>	
<b>BATTERY CX12</b>	Starting Type 24V/60Ah (C20)	Large autonomy lead acid deep cycle 24V/60Ah (C20)		-
<b>BATTERY CX14</b>	Starting Type 24V/70Ah (C20)	Large autonomy AGM deep cycle 24V/90Ah (C5) 110Ah (C20)		Lithium 24V/50Ah (C5) <b>LI-ION</b>
<b>BATTERY CHARGER</b>	On-board			

## EX Electric pallet trucks



### EX15

Compact and reliable EPT for light duty use

**Equipment:**

- ERGONOMIC TILLER WITH BATTERY STATUS INDICATOR AND HOURMETER
- HEAVY DUTY FORK CARRIAGE
- POWERFUL 0,65 KW DRIVE MOTOR
- BATTERY 24V/65AH
- ON BOARD BATTERY CHARGER
- FRONT REMOVABLE BATTERY COVER



1500 kg



1150 mm



560-685 mm



4,5 km/h

L2: 488 mm

Aisle width (EPAL): 1939 mm

Drive and lift: electric

## QX Electric pallet trucks



### QX20 EVO

Pedestrian driven heavy-duty EPT with powerful traction battery, high performance

**Equipment:**

- ERGONOMIC TILLER WITH 8 LEVELS BATTERY STATUS INDICATOR
- HOURMETER
- HEAVY DUTY FORK CARRIAGE
- POWERFUL AC DRIVE TECHNOLOGY 1,1 KW MOTOR
- TRACTION BATTERY 24V/210AH
- VARIABLE SPEED DEPENDING ON THE TILLER WORKING POSITION TO ENSURE EASINESS OF USE

**Options (for both versions):**

- Li-ION battery 24V/210 Ah



### QX20P EVO

Platform high performance heavy-duty EPT with powerful traction battery and power steering

**Equipment:**

- ERGONOMIC TILLER WITH 8 LEVELS BATTERY STATUS INDICATOR
- HOURMETER
- HEAVY DUTY FORK CARRIAGE
- ELECTRIC POWER STEERING
- CUSHIONED STAND-ON FOLDABLE PLATFORM WITH SIDE ARMS
- POWERFUL AC DRIVE TECHNOLOGY 2,5 KW MOTOR
- TRACTION BATTERY 24V/375AH
- VARIABLE SPEED DEPENDING ON THE TURNING ANGLE

- Automatic battery refilling system

- Load Backrest



L2: 598 mm

Aisle width (EPAL): 2015 mm

Drive and lift: electric



2000 kg




1000-1150 mm



540-685 mm



6 km/h



L2 Platform closed/open: 710/1137 mm

Aisle width (EPAL) platform closed/open: 2184/2634 mm

Drive and lift: electric



2000 kg



1000-1150 mm



540-685 mm



12 km/h

## PALLET STACKERS

### MX Manual Pallet Stackers



Robust and resistant manual stacker

**Equipment:**

- 4 CURVES COVERED TILLER
- NYLON ROLLERS
- NYLON STEERING WHEELS
- PROPORTIONAL LOWERING VALVE
- FOOT BRAKE
- FOOT PEDAL



1150 mm



550 mm

### MX 5/10



500 kg



1000 mm

### MX 5/16



500 kg



1600 mm

### MX 10/16



1000 kg



1600 mm

Aisle width: 2166 mm

Drive and lift: manual