

According to EN131/7 is tested with 30 Kg overturning traction force at platform level



VIDEO



Fly Light

SAFETY & PROTECTION AT 360°



CLIMBING BY RUNGS

It complies with the European Standards EN131/7 on mobile platform ladders and offers a 360° guardrail protection and an advanced outriggers foldable system that allow to work near walls. Operator can climb on rungs.

- Reinforced non-skid aluminum platform (58x44 cm) with anti-opening system and 10 cm toeboard
- Integrated lockable telescopic stabilizers (2 opening positions)
- PVC reinforced non-skid rubber feet with ergonomic design
- Non-skid rungs: depth 30 mm - rung distance 30 cm
- It stands when closed (thickness 63 cm)
- Wheels for transportation diam. 150 mm
- 100 cm guardrail on all 4 sides
- Wide base (maximum stability)
- Anti-opening straps
- Removable handrails
- Climbing ramp 47 cm
- Sveltbag tool-bag
- Steel opening hinges
- Shrink-wrapped
- Front frame section 67 x 27 mm
- Back section 57 x 27 mm



Including bag tools holder



Flanged, ribbed ergonomic rungs



Wheels Ø 150 mm



Pvc rubber feet



Foldable telescopic outriggers



cm 63



Anti-opening belt for transport



Large painted steel hinges



n.	m	m	m	cm	Kg	m
3	0,72	1,75	2,72	64x118	21,0	1,87
4	1,00	2,03	3,00	64x150	22,0	2,17
5	1,28	2,31	3,28	64x172	23,0	2,47
6	1,56	2,59	3,56	64x172	24,0	2,77
7	1,84	2,87	3,84	64x172	25,0	3,07

The platform is included in the number of steps

- The outriggers are foldable to work in narrow spaces.
- Handrails are patented. They can be quickly folded to transport the ladder.

Fly

SAFETY & PROTECTION AT **360°**



According to EN131/7 is tested with 30 Kg over-turning traction force at platform level



VIDEO



It complies with the European Standards EN131/7 on mobile platform ladders and offers a 360° guardrail protection and an advanced outriggers foldable system that allow to work near walls. Operator can climb on comfortable large steps.

- Reinforced non-skid aluminum platform (60x53 cm) with anti-opening system and 10 cm toeboard
- PVC reinforced non-skid rubber feet with ergonomic design
- Integrated lockable foldable telescopic stabilizers
- Non-skid steps: depth 80 mm step distance 26 cm
- Wheels for transportation diam. 150 mm
- It stands when closed (thickness 46 cm)
- 100 cm guardrail on all 4 sides
- Wide base (maximum stability)
- Anti-opening hook
- Patented foldable handrails
- Climbing ramp 55 cm
- Sveltbag tool-bag
- Steel opening hinges
- Thermo-shrinkable plastic package
- Front frame section 80 x 25 mm
- Back section 57 x 27 mm



Including bag tools holder



Large steps mm 80



Wheels Ø 150 mm



Foldable patented guardrails



Foldable telescopic outriggers



cm 46



Reinforcements on all step



Large painted steel hinges



n.	m	m	m	cm	Kg	m
3	0,75	1,77	2,75	72x134	22,0	1,99
4	1,00	2,02	3,00	72x155	23,5	2,25
5	1,26	2,29	3,26	72x178	25,0	2,55
6	1,52	2,54	3,52	72x199	26,5	2,83
7	1,78	2,80	3,78	72x225	28,0	3,11
8	2,03	3,05	4,03	72x246	29,5	3,39

The platform is included in the number of steps

- The outriggers are foldable to work in narrow spaces.
- Handrails are patented. They can be quickly folded to transport the ladder.

Telefly

According to EN131/7 is tested with 30 Kg overturning traction force at platform level

TELESCOPIC! CLIMBING BY LARGE STEPS



SAFETY & PROTECTION AT **360°**

MADE IN ITALY

RANGE **TOP**



ISO 9000
UNI EN 287/1
EN ISO 9606/2



- Equipped with a combination of 80 mm flat steps and 27 mm rungs. They give to the operator a maximum foot support of 134 cm
- Passage wheel to pass through narrow doors with the ladder
- Integrated foldable telescopic outriggers allow to work by the wall.

n.	min. m	max m	max m	cm	Kg	m
4	1,00	1,50	3,50	89x199	28,0	2,26
5	1,25	1,75	3,75	89x221	31,0	2,54
6	1,50	2,00	4,00	89x244	34,0	2,82

The platform is included in the number of steps

- Front frame section 80 x 25 mm
- Back section 57 x 27 mm

It complies with the European Standards EN131/7 on mobile platform ladders and offers a 360° guardrail protection and an advanced outriggers foldable system that allow to work near walls. Operator can climb on large steps. It combines all the features of a telescopic ladder with those of a mobile platform ladder, getting a mix of maneuverability, portability and safety that cannot be found in other models. Thanks to the telescopic system you can get 3 different working heights on each of the 4 models (12 heights overall) and can be used on stairs or steps. It allows easy transportation and can be opened in seconds.

- Reinforced non-skid aluminum platform (60x53 cm) with anti-opening system and 10 cm toeboard
- PVC reinforced non-skid rubber feet with ergonomic design
- Distance between steps 28 cm
- 100 cm guardrail on all 4 sides
- Enlarged base (maximum stability)
- Anti-opening hook
- It stands when closed
- Climbing ramp 55 cm
- Steel opening hinges
- Thermo-shrinkable plastic package



Including bag tools holder



Large steps from mm 270 to mm 134



Wheels Ø 150 mm



Foldable patented guardrails



Foldable telescopic outriggers





TELESCOPIC!
CLIMBING
BY RUNGS

Telefly Light



SAFETY &
PROTECTION AT
360°



VIDEO



PATENTED

Capacity
150
Kg

GUARANTEE
5
YEARS



ISO 9000
UNI EN 287/1
EN ISO
9606/2

EN131
TESTED BY
TÜV

It complies with the new European Standards EN131 and combines all the features of a telescopic ladder with those of a platform mobile ladder, getting a mix of maneuverability, portability and safety that cannot be found in other models. Thanks to the telescopic system you can get different working heights on each of the 2 models (7 heights overall) and can be used on stairs or steps. It allows easy transportation and can be opened in seconds.

- Reinforced non-skid aluminum platform (49x44 cm) with anti-opening system and 10 cm toeboards
- PVC reinforced non-skid rubber feet with ergonomic design
- Safety steel/nylon hooks for telescopic elevation
- It stands when closed (thickness 31 cm)
- Enlarged base (maximum stability)
- Non-skid steps 27x27 mm
- 100 cm guardrail
- Patented foldable handrails
- Climbing ramp 55 cm
- Transport locking strap
- Steel opening hinges
- Tool-holder 15 kg capacity
- Thermo-shrinkable plastic package



Anti-opening belt for transport




Large painted steel hinges



Wheels Ø 150 mm



Foldable patented guardrails



Tools holder foldable platform capacity Kg 15

On demand:

2 Foldable outriggers (installation by the company)



n.	min. m	max. m	max m	cm	Kg	m
4+3	1,00	1,52	3,50	80x160	17,5	2,15
6+4	1,52	2,32	4,30	80x217	20,5	2,73

The platform is included in the number of steps

- Outer profile section 64 x 30 mm
- Inner profile 57 x 27 mm



cm 31

