



P2



STEPS ON FRONT SIDE AND RUNGS ON BACK SIDE

Double sided professional stepladder with steps on one side and rungs on the other. Steps 8 cm, rungs 2,7 cm.



n.	m	m	cm	Kg
4 (3+platform)	1,23	0,94	47,00	5,2
5 (4+platform)	1,48	1,17	49,00	6,4
6 (5+platform)	1,72	1,41	51,50	7,5
7 (6+platform)*	1,98	1,64	54,50	9,2
8 (7+platform)*	2,23	1,87	56,00	10,3

* with safety steps

- Polypropylene platform/tool-holder (25,5 x 28 cm)
- Distance between steps 25 cm
- Reinforced non-skid rubber feet
- Thermo-shrinkable plastic package with showcard
- Front frame section mm 80x25
- Back frame section mm 40x20



VIDEO

Handrails on demand: m 0,6 (SCOR0602)
m 1,0 (SCOR1002) - m 1,5 (SCOR1502) - m 2,0 (SCOR2002)



Optional reinforcements on all steps



P3



VIDEO

One-sided aluminium stepladder. Steps 8 cm



n.	m	m	cm	Kg
3	1,11	1,00	45,00	3,9
4	1,38	1,23	47,00	4,7
5	1,63	1,46	49,50	5,3
6	1,88	1,69	52,00	6,6
7	2,13	1,92	54,50	7,3
9	2,61	2,38	59,50	10,0
11	3,11	2,84	64,50	12,0

The tool-holder is not included in the number of steps

The European standard EN131 forbids to stand on the last 2 steps when there are no platform and guardrail.

Handrails on demand: m 0,6 (SCOR0602) - m 1,0 (SCOR1002)
m 1,5 (SCOR1502) - m 2,0 (SCOR2002)

- Non-skid aluminium steps
- Reinforcing bars under the longest step
- Profile 80x25 mm
- Polypropylene tool-holder
- Anti-opening/closing bars
- Reinforced non-skid rubber feet
- Thermo-shrinkable plastic package with showcard



Optional reinforcements on all steps

