




Alpiluxe

Ladder in ribbed flanged natural aluminium. It is equipped with non-skid knurled rungs on both sides and base stabiliser and can be used as a stepladder or lean-to wall ladder.

TECHNICAL FEATURES

Rungs n°	Closed m	Stepladder m	Extended m	Profile mm	Base stabiliser cm	Weight Kg
6+6	1,84	1,78	3,62	57x27	65	9,0
7+7	2,12	2,04	4,18	57x27	65	10,5
8+8	2,40	2,30	4,74	57x27	73	12,0



Positions for use

Base section width 42,3 cm

- Non-skid knurled rungs
- Base stabiliser
- Distance between rungs 28 cm
- Non-skid rubber feet
- Thermo-shrinkable plastic package with showcard

The quick positioning hinge allows:

- opening and closing as a stepladder without modifying hinge position
- blocking ladder when used as a stepladder modifying hinge position
- opening/closing the ladder for use against walls by modifying hinge position



Brava

Double sided professional ladder in ribbed aluminium equipped with non-skid flanged rungs on both sides.

TECHNICAL FEATURES

Rungs n°	Closed m	Stepladder m	Base stabiliser cm	Profile mm	Weight Kg
8	2,33	2,20	73	57x27	10,0



Base stabiliser

Base section width 42,3 cm

- Nylon hinges
- Anti-opening hinges and safety straps
- Base stabiliser with rubber feet
- Non-skid flanged rungs 27x27 mm
- Distance between rungs 28 cm
- Non-skid rubber feet
- Thermo-shrinkable plastic package with showcard

