



P3

One-sided aluminium stepladder.

TECHNICAL FEATURES

Steps n°	Closed m	Stepladder m	Working height m	Base width cm	Weight Kg
3	1,11	1,00	2,21/2,41	45,00	3,9
4	1,38	1,23	2,44/2,64	47,00	4,7
5	1,63	1,46	2,67/2,87	49,50	5,3
6	1,88	1,69	2,90/3,10	52,00	6,6
7	2,13	1,92	3,13/3,33	54,50	7,3
9	2,61	2,38	3,59/3,79	59,50	10,0
11	3,11	2,84	4,05/4,25	64,50	12,0

The tool-holder is not included in the number of steps



Tool-holder

- Non-skid aluminium steps
- Reinforcing bars under the longest step
- Profile 80x25 mm
- Polypropylene tool-holder
- Anti-opening/closing bars
- Reinforced non-skid rubber feet
- Thermo-shrinkable plastic package with showcard



GL/C

Welded professional single section aluminium ladder. It is equipped with tool-holder.

TECHNICAL FEATURES

Steps n°	m	Working height m	Profile mm	Base width cm	Weight Kg
8	2,16	2,86	80x25	51,00	4,5
10	2,66	3,36	80x25	54,00	6,0
12	3,16	3,86	80x25	57,50	7,5
14	3,66	4,36	80x25	60,00	9,0
16	4,16	4,86	80x25	63,50	10,0
18	4,66	5,36	80x25	66,00	12,0

The tool-holder is included in the number of steps



Tool-holder

- Hooks for shelving on request
- Non-skid knurled steps 8 cm
- Step distance 25 cm
- Reinforced non-skid rubber feet
- Convergent frames
- Reinforcing bars under the longest steps
- Profile 80x25 mm
- Thermo-shrinkable plastic package with showcard